This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020).

SAFETY DATA SHEET



1. Identification

| Product name | : Mortein Fast Knockdown Fly & Mosquito Killer Odourless Aerosol | |
|--|---|--|
| SDS no. | : D0067111 | |
| Formulation # | : FF0102281 | |
| Supplier | : AUSTRALIA RB (Hygiene Home) Australia Pty Ltd 680 George St , Sydney, NSW 2000 Tel: +61 (0)2 9857 2000 | |
| | NEW ZEALAND RB (Hygiene Home) New Zealand Limited 2 Fred Thomas Drive, Takapuna Auckland , New Zealand 0622 Tel: +64 9 484 1400 | |
| Poison Information contact: | : Australia - 13 11 26 New Zealand - 0800 764 766 or 0800 POISON | |
| <u>Uses</u> | | |
| Product use | : Household insecticide. Consumer uses. | |
| 2. Hazard identif | ication | |
| Classification of the substance or mixture | : FLAMMABLE AEROSOLS - Category 1 SKIN CORROSION/IRRITATION - Category 2 | |
| GHS label elements Hazard pictograms | | |
| Signal word | : DANGER | |
| Hazard statements | : Extremely flammable aerosol. Causes skin irritation. | |

| | Causes skin irritation. | |
|--------------------------|--|--------|
| Precautionary statements | | |
| General | Keep out of reach of children. If medical advice is needed, have product con or label at hand. | tainer |
| Prevention | Keep away from heat, hot surfaces, sparks, open flames and other ignition so No smoking. Do not spray on an open flame or other ignition source. Do not or burn, even after use. Wash hands thoroughly after handling. | |
| Response | Not applicable | |
| Storage | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 ° | F. |
| Disposal | Dispose of contents and container in accordance with all local, regional, natio and international regulations. | nal |

3. Composition/information on ingredients

Substance/mixture

: Mixture

| Ingredient name | % (w/w) | CAS number |
|------------------|-----------|------------|
| n-butane | ≥10 - ≤30 | 106-97-8 |
| propane | ≥10 - ≤30 | 74-98-6 |
| Isobutane | ≥10 - ≤30 | 75-28-5 |
| isopentane | ≤3 | 78-78-4 |
| permethrin (ISO) | ≤0.1 | 52645-53-1 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

4. First-aid measures

| Description of necessary first aid measures | | | |
|---|---|--|--|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. | | |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. | | |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. | | |
| Ingestion | : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. | | |

| cts, acute and delayed | | | |
|--|--|--|--|
| | | | |
| No known significant effects or critical hazards. | | | |
| Toxic if inhaled. | | | |
| Causes skin irritation. | | | |
| No known significant effects or critical hazards. | | | |
| Over-exposure signs/symptoms | | | |
| No specific data. | | | |
| No specific data. | | | |
| Adverse symptoms may include the following: irritation redness | | | |
| | | | |

Date of issue

Г

4. First-aid measures Ingestion : No specific data.

| Indication of immediate me | lical attention and special treatment needed, if necessary |
|----------------------------|--|
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

See toxicological information (Section 11)

| 5. Fire-fighting measures | | |
|--|---|--|
| Extinguishing media | | |
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | |
| Unsuitable extinguishing media | : None known. | |
| Specific hazards arising from the chemical | : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. | |
| Hazardous thermal decomposition products | : No specific data. | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. | |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. | |
| Hazchem code | : Not applicable | |

6. Accidental release measures

| Personal precautions, protective equipment and emergency procedures | | | |
|---|--|--|--|
| For non-emergency : personnel | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. | | |
| For emergency responders : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". | | |

6. Accidental release measures

| Environmental precautions | : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage. |
|------------------------------|--|
| Methods and material for con | ntainment and cleaning up |
| Small spill | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. |
|--|--|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |
| Do not store above the following temperature | 50 °C |

8. Exposure controls/personal protection

| Control parameters |
|------------------------------|
| <u>Australia</u> |
| Occupational exposure limits |

| D0067111 | | | |
|--|-------------|---|---|
| 8. Exposure controls/personal protection | | | |
| Ingredient name | | | Exposure limits |
| Butane | | | Safe Work Australia (Australia, 1/2014). TWA: 1900 mg/m³ 8 hours. TWA: 800 ppm 8 hours. |
| New Zealand | | | |
| Occupational exposure lim | <u>its</u> | | |
| Ingredient name | | | Exposure limits |
| butane | | | NZ HSWA 2015 - GRWM 2016 (New Zealand, 2/2013). WES-TWA: 800 ppm 8 hours. WES-TWA: 1900 mg/m ³ 8 hours. |
| propane | | | NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2017). Oxygen Depletion [Asphyxiant]. |
| ethane | | | NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2017). Oxygen Depletion [Asphyxiant]. |
| Appropriate engineering controls | : | Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. | |
| Environmental exposure controls | : | they comply with the recases, fume scrubbers | tion or work process equipment should be checked to ensure quirements of environmental protection legislation. In some , filters or engineering modifications to the process ssary to reduce emissions to acceptable levels. |
| Individual protection meas | <u>ures</u> | | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. | |
| Eye/face protection | : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. | |
| Skin protection | | 0.00 | |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. | |
| Body protection | : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. | |
| Other skin protection | : | selected based on the t | nd any additional skin protection measures should be task being performed and the risks involved and should be at before handling this product. |

8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

| Appearance | | |
|---|---|----------------------------------|
| Physical state | 1 | Liquid. [Aerosol.] |
| Colour | : | White |
| Odour | : | Slightly paraffinic |
| Odour threshold | 1 | Not available. |
| рН | 1 | Not available. |
| Melting point/freezing point | 1 | Not available. |
| Boiling point, initial boiling point, and boiling range | : | Not available. |
| Flash point | : | Open cup: -60°C (-76°F) [Butane] |
| Evaporation rate | 4 | Not available. |
| Flammability | 4 | Not available. |
| Lower and upper explosion limit/flammability limit | : | Not available. |
| Vapour pressure | 1 | 240 kPa (1800.15 mm Hg) |
| Relative vapour density | 4 | Not available. |
| Relative density | 4 | Not available. |
| Solubility(ies) Not available. | : | |
| Not available. | | |
| Partition coefficient: n- octanol/water | : | Not applicable. |
| Auto-ignition temperature | 1 | Not available. |
| Decomposition temperature | 4 | Not available. |
| Heat of combustion | 4 | 19.94 kJ/g |
| Viscosity | 4 | Not available. |
| Particle characteristics | | |
| Median particle size | ÷ | Not applicable. |
| Aerosol product | | |
| Type of aerosol | 4 | Spray |
| | | 41 14 |

10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | : No specific data. |

| | _ | _ | |
|------|----|-------|--|
| Dato | of | issue | |
| Date | | 13346 | |

10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|---------------------------------|-----------------------|--------------------------|----------|
| Black Flag Odourless_FF0102281_D0067111_ANZ | LC50 Inhalation Vapour | Rat - Male, Female | 5.67 mg/l | 4 hours |
| | LD50 Dermal | Rat - Male | >2000 mg/kg | - |
| | LD50 Oral | Rat - Male | >2000 mg/kg | - |
| n-butane | LC50 Inhalation Vapour | Rat | 658000 mg/m ³ | 4 hours |
| Isobutane | LC50 Inhalation Vapour | Rat | 658000 mg/m ³ | 4 hours |
| isopentane | LC50 Inhalation Vapour | Rat | 280000 mg/m ³ | 4 hours |
| permethrin (ISO) | LC50 Inhalation Dusts and mists | Rat | >685 mg/m ³ | 3 hours |
| | LD50 Dermal | Rat | 1750 mg/kg | - |
| | LD50 Dermal | Rat | >2500 mg/kg | - |
| | LD50 Oral | Rat | 383 mg/kg | - |
| | LD50 Oral | Rat | 6000 mg/kg | - |

Conclusion/Summary

Not classified.Information is based on toxicity test result of the concentrate of a similar product.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|--|--------------------------|---------|-------|--------------|-------------|
| Black Flag Odourless_FF0102281_D0067111_ANZ | Eyes - Cornea opacity | Rabbit | 0 | - | 48 hours |
| | Skin - Moderate irritant | Rabbit | - | 4 hours | 14 days |
| permethrin (ISO) | Eyes - Mild irritant | Rabbit | - | - | - |
| | Skin - Mild irritant | Rabbit | - | - | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | | | | mg | |

Conclusion/Summary

Skin

Eyes

Causes skin irritation. Information is based on toxicity test result of the concentrate of a similar product.

Non-irritating to the eyes. Information is based on toxicity test result of the concentrate of a similar product.

Based on available data, the classification criteria are not met.

Respiratory

Sensitisation

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------------------|------------------------------|---|
| Black Flag Odourless_FF0102281_D0067111_ANZ | skin | Rabbit | Not sensitizing |
| permethrin (ISO) | skin | Guinea pig | Sensitising |
| Conclusion/Summary | | | |
| Skin | Non-sensitis similar produ | | on toxicity test result of the concentrate of a |
| Respiratory | Based on av | ailable data, the classific | ation criteria are not met. |
| <u>Germ Cell Mutagenicity</u> Not available. | | | |
| Conclusion/Summary Carcinogenicity Not available. | No known si | gnificant effects or critica | al hazards. |
| Conclusion/Summary <u>Reproductive toxicity</u> | No known si | gnificant effects or critica | al hazards. |
| Date of issue | : 26/05/202 | 23 | Page: 7/11 |

11. Toxicological information

Not available.

| | Conc | lusion | /Sum | mary |
|--|------|--------|------|------|
|--|------|--------|------|------|

No known significant effects or critical hazards.

Teratogenicity

Not available.

Conclusion/Summary No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

| Name | | Route of exposure | Target organs |
|------------|------------|----------------------|------------------|
| isopentane | Category 3 | - | Narcotic effects |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

| Name | Result |
|------------|--------------------------------|
| isopentane | ASPIRATION HAZARD - Category 1 |

Information on likely routes : Not available.

| of exposure | |
|---|--|
| Potential acute health effects | <u>5</u> |
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : Toxic if inhaled. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : No known significant effects or critical hazards. |
| Symptoms related to the phy | vsical, chemical and toxicological characteristics |
| Eye contact | : No specific data. |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| <u>Delayed and immediate effec</u> <u>Short term exposure</u> Potential immediate | ts as well as chronic effects from short and long-term exposure |
| effects | |
| Potential delayed effects | : Not available. |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health eff | <u>ects</u> |
| Not available. | |
| Conclusion/Summary | No known significant effects or critical hazards. |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Germ Cell Mutagenicity | : No known significant effects or critical hazards. |

Date of issue

11. Toxicological information

Teratogenicity

- : No known significant effects or critical hazards.
- Developmental effects Developmental effects
- No known significant effects or critical hazards.No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|----------------------|-----------|
| Inhalation (vapours) | 5.67 mg/l |

12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|------------------------------------|--|----------|
| permethrin (ISO) | Acute EC50 68 µg/l Marine water | Algae - Skeletonema costatum - Exponential growth phase | 96 hours |
| | Acute EC50 0.11 μg/l Fresh water | Crustaceans - Orconectes | 48 hours |
| | Acute EC50 0.151 ppb Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 0.0006 mg/l | Daphnia | 48 hours |
| | Acute LC50 0.0025 mg/l | Fish | 96 hours |
| | Acute LC50 0.62 µg/l Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| | Acute LC50 0.0018 mg/l | Fish - bluegill sunfish | 96 hours |
| | Chronic NOEC 0.039 ppb Fresh water | Daphnia - Daphnia magna | 21 days |
| | Chronic NOEC 0.3 ppb Fresh water | Fish - Pimephales promelas | 246 days |

Conclusion/Summary

Based on available data, the classification criteria are not met.

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| n-butane | 2.89 | - | low |
| propane | 1.09 | - | low |
| Isobutane | 2.8 | - | low |
| isopentane | 3 | 171 | low |
| permethrin (ISO) | 6.5 | - | high |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its

13. Disposal considerations

container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

| • | | | | |
|-------------------------------|--|---|---|--|
| | ADG | ADR/RID | IMDG | IATA |
| UN number | UN1950 | UN1950 | UN1950 | UN1950 |
| UN proper shipping name | AEROSOLS Marine Pollutant (Permethrin, Esbiothrin) | AEROSOLS Marine Pollutant (Permethrin, Esbiothrin) | AEROSOLS Marine Pollutant (Permethrin, Esbiothrin) | Aerosols, flammable Marine Pollutant (Permethrin, Esbiothrin) |
| Transport hazard class(es) | | | 2.1 | 2.1 |
| Packing group | 111 | 111 | | 111 |
| Environmental hazards | Yes. | Yes. | Yes. | Yes. |
| Additional information | tion | | · | · |
| ADG | : <u>Special</u> | provisions 63, 190, 277 | 7, 327, 344, 381 | |
| ADR/RID | | : <u>Special provisions</u> 63, 190, 277, 327, 344 <u>Tunnel code</u> (D) | | |
| IMDG | | : <u>Emergency schedules</u> F-D, S-U <u>Special provisions</u> 63, 190, 277, 327, 344, 381, 959 | | |
| ΙΑΤΑ | The environmentally hazardous substance mark may appear if required by other transportation regulations. <u>Quantity limitation</u> Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203. <u>Special provisions</u> A145, A167, A802 | | | |
| Special precautions | for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. | | | |
| Transport in bulk a | ccording : Not avail | able. | | |

to IMO instruments

Date of issue

: Not availabl

15. Regulatory information

| 15. Regulatory information | | | |
|--|--|--|--|
| Standard for the Uniform Scheduling of Medicines and Poisons | | | |
| Not scheduled | | | |
| Australian Inventory of Industrial Chemicals (AIIC) | All components are listed or exempted. | | |
| APVMA Number: | 60745 | | |
| New Zealand Inventory of Chemicals (NZIoC) | All components are listed or exempted. | | |
| HSNO Approval Number | HSR007755 | | |
| Approved Handler Requirement | No. | | |
| Tracking Requirement | No. | | |
| | | | |

: 26/05/2023

16. Other information

| Key to abbreviations | ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods GHS = Globally Harmonized System of Classification and Labelling of Chemicals IBC = Intermediate Bulk Container SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations SWA = Safe Work Australia HSNO = Hazardous Substances and New Organisms Act 1996 |
|----------------------------------|--|
| Date of issue / Date of revision | : 26/05/2023 |
| Version | : 2 |
| | (Version for undeted CHS Devision 7 DSDS Templete) |

(Version for updated GHS Revision 7 PSDS Template)

| Procedure used to derive the classification | |
|---|-----------------------|
| Classification | Justification |
| FLAMMABLE AEROSOLS - Category 1 | Expert judgment |
| SKIN CORROSION/IRRITATION - Category 2 | On basis of test data |
| | · · · · · |

References

: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Please read all labels carefully before using product.