SAFETY DATA SHEET



1. Identification

Product name : Mortein Powergard The Expert's Flying Insect Killer Aerosol

SDS no. : D8344045
Formulation # : FF8280455
Supplier : AUSTRALIA

RB (Hygiene Home) Australia Pty Ltd 680 George St , Sydney, NSW 2000

Tel: +61 (0)2 9857 2000

NEW ZEALAND

RB (Hygiene Home) New Zealand Limited

2 Fred Thomas Drive, Takapuna Auckland , New Zealand 0622

Tel: +64 9 484 1400

Poison Information contact: : Australia - 13 11 26

New Zealand - 0800 764 766 or 0800 POISON

Uses

Product use : Household insecticide

2. Hazard identification

Classification of the substance or mixture

: AEROSOLS - Category 1

SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 19.4%

GHS label elements
Hazard pictograms

:



Signal word : DANGER

Hazard statements : Extremely flammable aerosol. Pressurised container: may burst if heated.

Very toxic to aquatic life with long lasting effects.

Precautionary statements

General : Keep out of reach of children. If medical advice is needed, have product container

or label at hand.

Prevention: Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not

spray on an open flame or other ignition source. Pressurized container: Do not

pierce or burn, even after use.

Response : Collect spillage.

Storage : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Date of issue : 26/05/2023 Page: 1/11

D8344045

3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
Isobutane	≥30 - ≤60	75-28-5
n-butane	≥10 - ≤30	106-97-8
propane	≥10 - ≤30	74-98-6
tetramethrin (ISO)	<1	7696-12-0
allethrin	≤0.1	584-79-2
d-phenothrin	≤0.1	188023-86-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

4. First-aid measures

Description of necessary first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Date of issue : 26/05/2023 Page: 2/11

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazchem code : Not applicable

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue : 26/05/2023 Page: 3/11

6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Do not store above the following temperature

50 °C

8. Exposure controls/personal protection

Control parameters

Australia

Occupational exposure limits

Ingredient name	Exposure limits
Isobutane	ACGIH TLV (United States, 1/2022). [Butane] Explosive potential.
n-butane	STEL: 1000 ppm 15 minutes. Safe Work Australia (Australia, 12/2019). TWA: 1900 mg/m³ 8 hours.
propane	TWA: 800 ppm 8 hours. ACGIH TLV (United States, 1/2022). Oxygen Depletion [Asphyxiant]. Explosive potential.

New Zealand

Occupational exposure limits

Date of issue : 26/05/2023 Page: 4/11

8. Exposure controls/personal protection

Ingredient name	Exposure limits
Isobutane	ACGIH TLV (United States, 1/2022). [Butane] Explosive potential. STEL: 1000 ppm 15 minutes.
butane	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). WES-TWA: 800 ppm 8 hours. WES-TWA: 1900 mg/m³ 8 hours.
propane	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). Oxygen Depletion [Asphyxiant].

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue : 26/05/2023 Page: 5/11

Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>

Physical state : Liquid. [Aerosol.]

Colour Colourless to pale yellow

Odour : Citrus

: Not available. **Odour threshold** pH : Not available. **Melting point/freezing point** : Not available. **Boiling point, initial boiling** : Not available.

point, and boiling range

Flash point : Closed cup: -60°C (-76°F)

Evaporation rate Not available. **Flammability** : Not available. Lower and upper explosion : Not available.

limit/flammability limit

Vapour pressure Not available. : Not available. Relative vapour density **Relative density** : Not available.

0.77 g/cm³ [25°C (77°F)] **Density**

Solubility(ies)

Media Result cold water Not soluble Not soluble hot water

Partition coefficient: n-

octanol/water

: Not applicable.

: Not available. **Auto-ignition temperature Decomposition temperature** : Not available. **Heat of combustion** 36.27 kJ/a **Viscosity** : Not available.

Particle characteristics

Median particle size : Not applicable.

Aerosol product

Type of aerosol : Spray

10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue : 26/05/2023 Page: 6/11

11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isobutane	LC50 Inhalation Vapour	Rat	658000 mg/m ³	4 hours
n-butane	LC50 Inhalation Vapour	Rat	658000 mg/m ³	4 hours
tetramethrin (ISO)	LC50 Inhalation Vapour	Rat	>1.73 mg/l	4 hours
, ,	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	4640 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary

Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
tetramethrin (ISO)	Eyes - Mild irritant	Rabbit	-	1 hours 100	-
				mg	

Conclusion/Summary

SkinBased on available data, the classification criteria are not met.EyesBased on available data, the classification criteria are not met.RespiratoryBased on available data, the classification criteria are not met.

<u>Sensitisation</u>

Not available.

Conclusion/Summary

SkinBased on available data, the classification criteria are not met. **Respiratory**Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Not available.

Conclusion/Summary Based on available data, the classification criteria are not met.

Carcinogenicity

Not available.

Conclusion/SummaryBased on available data, the classification criteria are not met.

Reproductive toxicity

Not available.

Conclusion/Summary Based on available data, the classification criteria are not met.

Teratogenicity

Not available.

Conclusion/SummaryBased on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
tetramethrin (ISO)	Category 2	inhalation	nervous system

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Date of issue : 26/05/2023 Page: 7/11

11. Toxicological information

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/SummaryBased on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Germ Cell Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Date of issue : 26/05/2023 Page: 8/11

12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
tetramethrin (ISO)	Acute EC50 72.83 ug/ml Marine water	Crustaceans - Balanus albicostatus	48 hours
	Acute EC50 0.11 mg/l Acute EC50 45 ppb Fresh water Acute LC50 0.0037 mg/l Acute LC50 0.016 mg/l	Daphnia Daphnia - Daphnia magna Fish Fish - bluegill sunfish	48 hours 48 hours 96 hours 96 hours

Conclusion/Summary

Calculation method Very toxic to aquatic life with long lasting effects

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Isobutane	2.8	-	low
n-butane	2.89	-	low
propane	1.09	-	low
tetramethrin (ISO)	4.73	-	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

14. Transport information

	ADG	ADR/RID	IMDG	IATA	
UN number	UN1950	UN1950	UN1950	UN1950	
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable	
Transport hazard class(es)	2.1	2	2.1	2.1	
Packing group	-	-	-	-	

Date of issue : 26/05/2023 Page: 9/11

D8344045

14. Transport information

Environmental	Yes. The	Yes.	Yes.	Yes. The
hazards	environmentally			environmentally
	hazardous substance			hazardous substance
	mark is not required.			mark is not required.

Additional information

ADG : **Special provisions** 63, 190, 277, 327, 344, 381

ADR/RID : The environmentally hazardous substance mark is not required when transported in

> sizes of ≤5 L or ≤5 kg. Limited quantity 1 L

Special provisions 190, 327, 625, 344

Tunnel code (D)

IMDG The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Emergency schedules F-D, S-U

Special provisions 63, 190, 277, 327, 344, 381, 959

IATA The environmentally hazardous substance mark may appear if required by other

transportation regulations.

Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities -

Passenger Aircraft: 30 kg. Packaging instructions: Y203.

Special provisions A145, A167, A802

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled

Australian Inventory of Industrial Chemicals (AIIC) At least one component is not listed.

APVMA Number:

53236

New Zealand Inventory of

Chemicals (NZIoC)

All components are listed or exempted.

HSNO Approval Number

Approved Handler

Requirement

HSR100865 No

Tracking Requirement No

16. Other information

Key to abbreviations

: ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of

Dangerous Goods by Road

RID = The Regulations concerning the International Carriage of Dangerous Goods

by Rail

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IBC = Intermediate Bulk Container

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

SWA = Safe Work Australia

HSNO = Hazardous Substances and New Organisms Act 1996

Date of issue : 26/05/2023 Page: 10/11 D8344045

16. Other information

Date of issue / Date of

revision

: 26/05/2023

Version : 2.0L

(Version for updated GHS Revision 7 PSDS Template)

Procedure used to derive the classification

ClassificationJustificationAEROSOLS - Category 1On basis of test dataSHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1Calculation methodLONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1Calculation method

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Please read all labels carefully before using product.

Date of issue : 26/05/2023 Page: 11/11