This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020).

# SAFETY DATA SHEET



Product name SDS no.	: Glen 20 All in One Spray Disinfectant Lavender : D8399294
Formulation #	: FF3239685
Supplier	: AUSTRALIA RB (Hygiene Home) Australia Pty Ltd 680 George St , Sydney, NSW 2000 Tel: +61 (02) 9857 2000
	NEW ZEALAND RB (Hygiene Home) New Zealand Limited 2 Fred Thomas Drive, Takapuna, Auckland, New Zealand 0622 Tel: +64 9 484 1400
Poison Information contact:	: Australia - 13 11 26 New Zealand - 0800 764 766 or 0800 POISON
<u>Uses</u>	
Product use	: Disinfectant. Surface Cleaner. Consumer use

## 2. Hazard identification

<b>Classification of the</b>	: AEROSOLS - Category 1
substance or mixture	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A

2

### GHS label elements

Hazard pictograms



Signal word	DANGER
Hazard statements	Extremely flammable aerosol. Pressurised container: may burst if heated. Causes serious eye irritation.
Precautionary statements	
General	Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Do not pierce or burn, even after use.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.

reckitt

## 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	% (w/w)	CAS number	
ethanol	≥30 - ≤60	64-17-5	
n-butane	≥10 - ≤30	106-97-8	
propane	≤10	74-98-6	
Isobutane	≤10	75-28-5	
ethane	≤3	74-84-0	
isopentane	<2.5	78-78-4	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

## 4. First-aid measures

Description of necess	sary first aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.</li> </ul>
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health	h effects	
Eye contact	: Causes serious eye irritation.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs	/symptoms	
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	<ul> <li>Adverse symptoms may include the following: respiratory tract irritation coughing</li> </ul>	
Skin contact	: No specific data.	
Date of issue	: 10/03/2023	Page: 2/11

## 4. First-aid measures

Ingestion

```
: No specific data.
```

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### See toxicological information (Section 11)

5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
Specific hazards arising from the chemical	: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.	
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>	
Hazchem code	: Not applicable	

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

Date of issue	: 10/03/2023	Page: 3/11

## 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
Do not store above the following temperature	50 °C
8. Exposure contro	ls/personal protection

Control parameters
<u>Australia</u>
<b>Occupational exposure limits</b>

## 8. Exposure controls/personal protection

Ingredient name	Exposure limits
ethanol	Safe Work Australia (Australia, 12/2019).
	TWA: 1880 mg/m³ 8 hours.
	TWA: 1000 ppm 8 hours.
n-butane	Safe Work Australia (Australia, 12/2019).
	TWA: 1900 mg/m³ 8 hours.
	TWA: 800 ppm 8 hours.
propane	ACGIH TLV (United States, 1/2022). Oxygen Depletion
	[Asphyxiant]. Explosive potential.
Isobutane	ACGIH TLV (United States, 1/2022). [Butane] Explosive
	potential.
	STEL: 1000 ppm 15 minutes.
ethane	ACGIH TLV (United States, 1/2022). Oxygen Depletion
	[Asphyxiant]. Explosive potential.
isopentane	ACGIH TLV (United States, 1/2022). [Pentane]
	TWA: 1000 ppm 8 hours.

### New Zealand

### **Occupational exposure limits**

Ingredient name	Exposure limits
ethanol	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). WES-TWA: 1000 ppm 8 hours. WES-TWA: 1880 mg/m <sup>3</sup> 8 hours.
butane	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). WES-TWA: 800 ppm 8 hours. WES-TWA: 1900 mg/m³ 8 hours.
propane	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). Oxygen Depletion [Asphyxiant].
Isobutane	ACGIH TLV (United States, 1/2022). [Butane] Explosive potential. STEL: 1000 ppm 15 minutes.
ethane	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). Oxygen Depletion [Asphyxiant].
isopentane	ACGIH TLV (United States, 1/2022). [Pentane] TWA: 1000 ppm 8 hours.

Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls Individual protection measure	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
	-
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## 8. Exposure controls/personal protection

	• •
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance			
Physical state	:	: Liquid. [Liquefied compressed gas.]	
Colour	:	: Colourless to light yellow.	
Odour	:	: Fragrant.	
Odour threshold	:	: Not available.	
рН	:	: 7.4 to 9 [Conc. (% w/w): 100%]	
Melting point/freezing point	:	: Not available.	
Boiling point, initial boiling point, and boiling range	:	: Not available.	
Flash point	:	: Closed cup: <-18°C (<-0.4°F)	
Evaporation rate	1	: Not available.	
Flammability	1	: Not available.	
Lower and upper explosion limit/flammability limit	1	: Not available.	
Vapour pressure	:	: Not available.	
Relative vapour density	1	: Not available.	
Relative density	1	: 0.83 to 0.85	
Solubility(ies)	1	:	
Media		Result	
cold water hot water	_	Partially soluble Partially soluble	
Partition coefficient: n- octanol/water	:	: Not applicable.	
Auto-ignition temperature	:	: Not available.	
Decomposition temperature	3	: Not available.	
Date of issue		: 10/03/2023	Page: 6/11

## 9. Physical and chemical properties

Heat of combustion	: 33.56 kJ/g
Viscosity	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
Aerosol product	
Type of aerosol	: Spray

# 10. Stability and reactivity

	• · · ·	
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition should not be produced.	products
Incompatible materials	No specific data.	
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will no	ot occur.
Chemical stability	The product is stable.	
Reactivity	No specific test data related to reactivity available for this product or its i	ngredients.

## 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapour	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-
n-butane	LC50 Inhalation Vapour	Rat	658000 mg/m <sup>3</sup>	4 hours
Isobutane	LC50 Inhalation Vapour	Rat	658000 mg/m <sup>3</sup>	4 hours
isopentane	LC50 Inhalation Vapour	Rat	280000 mg/m <sup>3</sup>	4 hours

**Conclusion/Summary** Based on available data, the classification criteria are not met.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	Eyes - Moderate irritant	Rabbit	-	mg 0.066666667 minutes 100	-
	Eyes - Moderate irritant	Rabbit	_	mg 100 uL	_
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	

Date of issue	: 10/03/2023	Page: 7/11
Skin	Based on available data, the classification criteria are not met.	
Conclusion/Summary		
Not available.		
<u>Sensitisation</u>		
Respiratory	Based on available data, the classification criteria are not met.	
Eyes	Calculation method: Causes serious eye irritation.	
Skin	Based on available data, the classification criteria are not met.	
Conclusion/Summary		

## 11. Toxicological information

Respiratory	Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity	
Not available.	
Conclusion/Summary	Based on available data, the classification criteria are not met.
Carcinogenicity	
Not available.	
Conclusion/Summary	Based on available data, the classification criteria are not met.
Reproductive toxicity	
Not available.	
Conclusion/Summary	Based on available data, the classification criteria are not met.
<u>Teratogenicity</u>	

Not available.

**Conclusion/Summary** Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
isopentane	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
isopentane	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure	:	Not available.	
Potential acute health effects	<u>s</u>		
Eye contact	:	Causes serious eye irritation.	
Inhalation	:	No known significant effects or critical hazards.	
Skin contact	:	No known significant effects or critical hazards.	
Ingestion	:	No known significant effects or critical hazards.	
Symptoms related to the phy	/si	cal, chemical and toxicological characteristics	
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	:	No specific data.	
Ingestion	:	No specific data.	
Delayed and immediate effect	<u>cts</u>	as well as chronic effects from short and long-term exposure	
Short term exposure			
Potential immediate effects	:	Not available.	
Potential delayed effects	:	Not available.	
Date of issue		: 10/03/2023	Page: 8/11

## 11. Toxicological information

Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
Potential chronic health eff	<u>ect</u>	<u>s</u>
Not available. Conclusion/Summary		Based on available data, the classification criteria are not met.
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Germ Cell Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	1	No known significant effects or critical hazards.

# Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

### Acute toxicity estimates

Not available.

## **12.** Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 3306 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 1074 mg/l Fresh water	Crustaceans - Cypris subglobosa	48 hours
	Acute LC50 5680 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 11000000 μg/l Marine water	Fish - Alburnus alburnus	96 hours
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days

**Conclusion/Summary** Based on available data, the classification criteria are not met.

### Persistence and degradability

**Conclusion/Summary** 

Based on available data, the classification criteria are not met.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low
n-butane	2.89	-	low
propane	1.09	-	low
Isobutane	2.8	-	low
ethane	1.09	-	low
isopentane	3	171	low

### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

## **12.** Ecological information

Other adverse effects

: No known significant effects or critical hazards.

## 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## 14. Transport information

-				
	ADG	ADR/RID	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
Transport hazard class(es)	2.1	2	2.1	2.1
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

Additional information		
ADG	:	<b>Special provisions</b> 63, 190, 277, 327, 344, 381
ADR/RID	:	<u>Limited quantity</u> 1 L <u>Special provisions</u> 190, 327, 625, 344 <u>Tunnel code</u> (D)
IMDG	:	<u>Emergency schedules</u> F-D, S-U <u>Special provisions</u> 63, 190, 277, 327, 344, 381, 959
ΙΑΤΑ	:	Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions: 203. Cargo Aircraft Only: 150 kg. Packaging instructions: 203. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y203. Special provisions A145, A167, A802
Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

## 15. Regulatory information

### Standard for the Uniform Scheduling of Medicines and Poisons

Not scheduled Australian Inventory of Industrial Chemicals (AIIC)	All components are listed or exempted.
ARTG Number	AUST L 65954
New Zealand Inventory of Chemicals (NZIoC)	All components are listed or exempted.
HSNO Group Standard	Aerosols (Flammable.)
HSNO Approval Number	HSR002515
Approved Handler Requirement	Not applicable.
Tracking Requirement	Not applicable.

### **16.** Other information

Key to abbreviations	: ADG = Australian Dangerous Goods
Rey to appreviations	ADR = The European Agreement concerning the International Carriage of
	Dangerous Goods by Road
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals IBC = Intermediate Bulk Container
	SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations
	SWA = Safe Work Australia
	HSNO = Hazardous Substances and New Organisms Act 1996
Date of issue / Date of revision	: 10/03/2023
Version	: 1
	(Version for updated GHS Revision 7 PSDS Template)

#### Procedure used to derive the classification

Classification	Justification
AEROSOLS - Category 1	On basis of test data
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	Calculation method

References : Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Please read all labels carefully before using product.